

Revision Date: 05/07/2024

Version: 1

Page: 1 of 9

NEXSTGE® True Soak Off UV Top Coat

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURES AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name NEXSTGEN® True Soak Off Top Coat

1.2. Relevant identified uses of the substance or mixture and uses advised against

For use on nail applications.

1.3. Details of the supplier of the safety data sheet

Supplier St. George Technology, inc.

210 N. Green Meadows Drive

Wilmington, NC 28405

United States 910-397-0781

sales@stgeorgetecnology.com

1.4. Emergency contacts

Office Hours St. George Technology, Inc.

M-F 8:00-5:00 EST

Out of Hours INFOTRAC 800-535-5053

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

This substance is classified as hazardous according to GHS

H225	Flammable Liquids	Hazard category 2
H315	Irritation of skin	Hazard category 2
H317	Skin sensitisation	Hazard category 1B
H319	Causes serious eye irritation	Hazard category 2A
H302	Harmful if swallowed	Hazard category 4

2.2. Label elements

Signal word Danger (Code: Dgr)

GHS Pictogram





H315 H317

Hazard Statement H225 Highly flammable liquid or vapour

H315 Causes skin irritation

H317 May cause an allergic skin reaction H319 Causes serious eye irritation

Precautionary Statement



Revision Date: 05/08/2022

Version: 1 Page: 2 of 9

NEXSTGEN® True Soak Off UV Top Coat

(Prevention)	P233 Keep P242 Use P264 Was P270 Dor	p away from flames and hot surfaces. No smoking. p container tightly closed. only non-sparking tools. th skin thoroughly after handling. not eat, drink or smoke when using this product. ar protective gloves.
(Response)	P303+361+353 P305+ P351 + P338	IF ON SKIN (or hair): Remove/Take off immediately all clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
(Store) (Disposal)	P332+ P313 P361 P371+ P378 P403+P235 P501	If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before use. In case of fire: Use appropriate media for extinction. Store in a well ventilated place. Keep cool Dispose of contents/container in accordance with local regulation

2.3. Other hazards

Polymerisation with heat evolution may occur

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

In Accordance with Regulation EC 1272/2008

COMPONENT	CAS NO.	CONTENT	HAZARD/CATEGORY/STATEMENT
Thioether acrylate oligomer	N/A	< 50	H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 – Causes serious eye irritation
Pentaerythritol tetra (3-mercaptopropionate)	7575-23-7	< 20	H302 - Harmful if swallowed H317 - May cause an allergic skin reaction. H410 - Very toxic to aquatic life with long lasting effects.
Di-trimethylolpropane tetraacrylate	94108-97-1	< 20	H319 – Causes serious eye irritation H411 – Toxic to aquatic life with long lasting effects
Cellulose acetate butyrate	9004-36-8	< 20	N/A
Polyester acrylate	N/A	< 10	H315 - Causes skin irritation H319 – Causes serious eye irritation
Tetrahydrofuryl methacrylate	2455-24-5	< 10	H317 - May cause an allergic skin reaction. H412 - Harmful to aquatic life with long lasting effects.
Hydroxypropyl methacrylate	27813-02-1	< 10	H317 – May cause an allergic skin reaction H319 – Causes serious eye irritation
Butyl Acetate	123-86-4	< 10	H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.
Ethyl Acetate	141-78-6	< 10	H225 – highly flammable liquid and vapour



Revision Date:05/08/2024

Version: 1

Page: 3 of 9

NEXSTGEN® True Soak Off UV Top Coat

			H319 – Causes serious eye irritation H336 – May cause drowsiness or dizziness
Ethyl Trimethylbenzoyl Phenylphosphinate	84434-11-7	< 5	H317 - May cause an allergic skin reaction H411 - Toxic to aquatic life with long lasting effects

4. FIRST AID MEASURES

4.1. Description of first aid measures

General advice Medical treatment is necessary if symptoms occur which are obviously caused by skin or

eye contact with the product, or by vapour inhalation. Remove soiled soaked clothing

immediately.

Inhalation Move casualty to fresh air and keep them calm. Seek medical attention.

Skin contact Wash off immediately with soap and water. If skin irritation occurs, seek medical

attention.

Eye contact Holding eyelids open, immediately rinse thoroughly with plenty of water. Seek medical

advice.

Ingestion Do not induce vomiting. Immediately contact a doctor.

Self protection of first-aider No specific protection is required. Gloves are recommended.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin and eye irritation. Skin sensitisation.

4.3. Indication of any immediate medical attention and special treatment needed

Seek immediate medical attention if symptoms indicate excessive exposure to eyes or skin.

5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Foam, dry powder, carbon dioxide

Unsuitable extinguishing media Water

5.2. Special hazards arising from the substance or mixture

No

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse.



Revision Date:05/08/2022

Version: 1

Page: 4 of 9

NEXSTGEN® True Soak Off UV Top Coat

6.2. Environmental procedures

Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. Do not allow to enter drains/surface water/ground water/sewerage systems. If entry occurs IMMEDIATELY alert The Environment Agency or other equivalent appropriate body.

6.3. Methods and material for containment and cleaning up

Larger volumes: remove mechanically (by pumping). Use explosion-proof equipment. Smaller volumes and/or residues: contain with absorbent material (e.g. sand, diatomaceous earth, acid absorbent, universal absorbent or sawdust). Dispose of in accordance with local regulations.

6.4. Reference to other sections

For personal protection see section 8. For disposal considerations see section 13.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Measures to Prevent Fire

Ensure the area is well ventilated. Keep container tightly closed. Keep away from heat, sparks and open flame – no smoking. When heated above the flashpoint and/or during spraying (atomising), ignitable mixtures may form in air.

Measures to Protect the Environment

Avoid spills. Keep substance away from drains to sewer. Keep the container tightly closed.

General Occupational Hygiene

Do not eat, drink or smoke in work areas. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions of safe storage, including any incompatibilities

Keep only in the original container. Protect from light. Fill the container by approx. 90% only as oxygen (air) is required for stabilisation. With large storage containers, ensure oxygen supply is sufficient to allow stability. Can polymerise with heat release.

7.3. Specific end use(s)

No

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Exposure Limits - There are no exposure limits identified for this product

General protective measures:

Keep away from heat, sparks and flame. Do not inhale vapours. Avoid contact with eyes and skin. Keep container closed after each use. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling product.



Revision Date: 05/08/2024

Version:

Page: 5 of 9

NEXSTGEN® True Soak Off UV Top Coat

Personal Protective Equipment 8.3.

Store work clothes separately. Remove soiled or soaked clothing immediately. Follow Hygiene measures

the usual good standards of occupational hygiene. Clean skin thoroughly after handling.

Apply skin cream.

Respiratory protection If ventilation is insufficient, breathing apparatus (e.g. EN140) to be used in case of high

concentrations, short term: filter appliance, filter A, e.g. EN141

Hand protection Impermeable gloves, suitable glove type should be selected for each work environment.

Gloves should be replaced regularly, especially after extended contact with the

substance.

Eye protection Safety glasses

Body protection As required to minimize skin contact. Rubber Apron. Eye wash, safety shower

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Form Liquid

Colour Clear

Odour ester-like

Melting Temperature Not Known

Boiling Temperature (low-high) 100°C

Flashpoint Not Known

Not Known Ignition Temperature

Vapour Pressure Not Known

Relative Density 1.17

Relative Vapour Density Not Known

Solubility in Water Insoluble

Solubility (Qualitative) Miscible with most organic solvents

pH value Not applicable

Viscosity 1500 - 4000 cP

Other information

None

10. STABILITY AND REACTIVITY



Revision Date: 05/08/2024

Version: 1

Page: 6 of 9

NEXSTGEN® True Soak Off UV Top Coat

10.1. Reactivity

Refer to sections 2.3 and 10.2

10.2. Chemical stability

Stable under normal temperature conditions and when used as directed. No decomposition occurs when used as directed.

10.3. Possibility of hazardous reactions

Refer to section 2.3.

10.4. Conditions to avoid

The substance is normally supplied in a stabilised form. If the permissible storage period/storage temperature is exceeded, the product may polymerise with heat generation. Avoid excessive heat for long periods of time. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

None

10.6. Hazardous decomposition products

No decomposition occurs when used as directed.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Eye Irritation: May cause eye irritation. Avoid eye contact. Direct contact with this product may cause burning, tearing, redness, and swelling

Skin Corrosion/Irritation: Not irritating under normal use. Do not use on broken or damaged skin.

Respiratory or Skin Sensitization: Not a skin sensitizer.

Acute toxicity: Not Available

Germ Cell Mutagenicity: Does not contain any ingredients known to be mutagenic according to OSHA

Carcinogenicity: Does not contain any ingredients known to be carcinogenic according to OSHA, NTP, and IARC

12. ECOLOGICAL INFORMATION

This product has not been tested as a whole for environmental toxicity. However, environmental information on the ingredients in this product have been reviewed by the Global Product Safety and Regulatory Department of Revlon and determined to have an acceptable environmental profile.

Aquatic Toxicity: Not expected to cause aquatic toxicity

Persistence and Degradability: Not Available

Bioaccumulative Potential: Not Available

Mobility in Soil: Not Available

Other Adverse Effects: Not expected to cause adverse effects



Revision Date: 05/08.2024

Version: 1

Page: 7 of 9

NEXSTGEN® True Soak Off UV Top Coat

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local state and federal regulations. Container disposal, offer for recycling or triple rinse and dispose of in an approved landfill.

14. TRANSPORT INFORMATION

14.1. UN number UN 1263 Hazard Class 3, flammable liquids Packing Group III

14.2. **UN proper shipping name** Paint

Land Transport ADR/GGVSEB UN/Germany

UN 1263 Flammable Liquid, N.O.S. Class 3, Group II, Tunnel restriction code D/E

Land Transport RID/GGVSEB

UN 1263 Flammable Liquid, N.O.S., Class 3, Group II

Inland Waterway Transport ADNR/GGVSEB

UN 1263 Flammable Liquid, N.O.S., Class 3, Group II

Shipment by Sea IMDG/GGVSee

UN 1263 Flammable Liquid, N.O.S., Class 3, Group II

Air Transport ICAO/IATA

UN 1263 Flammable Liquid, N.O.S., Class 3, Group II

14.3. Transport hazard class(es)

Refer to section 14.2

14.4. Packing group

Refer to section 14.2

14.5. Environmental hazards

Refer to section 14.2, not applicable if unmentioned

14.6. Special precautions for user

Refer to section 14.2

14.7. Transport in bulk according to the IBC code

Revision Date 05/08/2024

Version: 1
Page: 8 of 9

NEXSTGEN® True Soak Off UV Top Coat

For transport approval see regulatory information

MARPOL 73/78, Annex II – Regulations for Control of Pollution by Noxious Liquid Substances in Bulk

SOLAS Chapter VII – Carriage of Dangerous Goods

15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

COMMISSION REGULATION (EC) 2018/1480 of 4 October 2018 amending, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures and correcting Commission Regulation (EU) 2017/776.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

National Legislation

Occupational Restrictions Note for juveniles

Note for pregnant women and nursing mothers

EC Directive 92/85/EEC

Status of Registration REACH (EU) registered/pre-registered

TSCA (USA) listed or exempt
DSL (CDN) listed or exempt
AICS (AUS) listed or exempt
METI (J) listed or exempt
ECL (KOR) listed or exempt
PICCS (RP) listed or exempt
IECSC (CN) listed or exempt

HSNO (NZ) listed or exempt Code: HSR001195

15.2. Chemical safety assessment

Hazard symbols	F	Flammable
	Xi	Harmful

H-statements from Section 3 H225 Highly flammable liquid or vapour

H315 Causes skin irritation

H317 May cause an allergic skin reaction H319 Causes serious eye irritation

16. OTHER INFORMATION

The substance is normally supplied in a stabilised form.

If the permissible storage period and/or storage temperature is noticeably exceeded, the substance may polymerise with heat evolution.

The instructions given here are valid only for the substance as supplied, not for derivatives resulting from its use.

Revision Date 05/08/2024

Version: 1

Page: 9 of 9

NEXSTGEN® True Soak Off UV Top Coat

References Quoted manuals and standards

IMO

OECD-SIDS

SIAR NIH NIOSH OHSA UNECE

Revision

This datasheet has been re-written and replaces all previous versions. The information and all further technical advice is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the substances in terms of their safety and handling requirements. The instructions given here are valid only for the product as supplied, not for derivatives resulting from its use. It implies no liability or other legal responsibility on our part. In particular, no warranty, whether expressed or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection of incoming goods.

END OF SAFETY DATA SHEET